



386 Internationale Drive Suite H, Bolingbrook, Illinois 60440  
 Tel: (630) 633-4500 Toll Free: (800) 379-1191 Fax: (630) 296-8100

## CCTV Security Camera SmartWire™

UL Listed and Rated CMR or CMG

P/N 659111 - Type RG 59/U Non-Plenum, 20 AWG Bare Copper  
 95% Bare Copper Braid



Cable Specifications	
Description:	Type RG 59/U, Non-Plenum, 20 AWG Solid Bare Copper Center Conductor with a 95% Bare Copper Braid, UL Listed Type CMR/CMG
Conductor:	20 AWG Solid Bare Copper
Dielectric:	Foam Polyethylene
Shield:	95% Bare Copper Braid
Jacket:	PVC
Marking:	CLOSED CIRCUIT VIDEO SURVEILLANCE CAMERA CABLE CAMERA / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 20 AWG RG 59/U CCTVR CMG, CMR C(UL) US 75C
Overall Diameter:	.242" Nom.
Capacitance:	16.2 pF/ft. Nom.
Impedance:	75 Ohms
Velocity of Propagation:	83%
Temperature / Voltage:	75 C / 300 Volt
Cable Weight:	36 Lbs/Mft.



### Flame Rating:

N/A

### Agencies Approvals:

Power Limited Circuit Cable, Class 2, UL Type CMR/CMG, C(UL),  
 RoHS Compliant

